
Configure Documentation

Release 2.1

Antoine Millet

October 12, 2016

Contents

1	Features	3
2	Example	5
3	Contents	7
3.1	Schema validation API	7
3.2	Tips ‘n Tricks	14
4	Indices and tables	19

Confiture (formerly Dotconf) is an advanced configuration parsing library which can be used by developers who are limited with standard ConfigParser library. Confiture is also shipped with a schema validator which can be used to check the content of your application's configuration file before to start.

Features

- Simple configuration format with sections
- Typing:
 - Typing in the syntax (“42” is a string, 42 a number)
 - Four types available: string, boolean, number or list
- Validation of configuration using a schema
- Configuration includes

Example

This is an example of what you can do with Confiture:

```
from confiture.schema.containers import many, once
from confiture.schema.containers import Section, Value
from confiture.schema.types import Boolean, Integer, Float, String

# Schema definition:

class UserSection(Section):
    password = Value(String())
    _meta = {'repeat': many, 'unique': True}

class PathSection(Section):
    rate_limit = Value(Float(), default=0)
    enable_auth = Value(Boolean(), default=False)
    user = UserSection()

class VirtualHostSection(Section):
    enable_ssl = Value(Boolean(), default=False)
    path = PathSection()
    _meta = {'repeat': many, 'unique': True}

class MyWebserverConfiguration(Section):
    daemon = Value(Boolean(), default=False)
    pidfile = Value(String(), default=None)
    interface = Value(String(), default='127.0.0.1:80')
    interface_ssl = Value(String(), default='127.0.0.1:443')
    host = VirtualHostSection()
```

Then, to use the parser:

```
>>> conf = '''
... daemon = yes
... pidfile = '/var/run/myapp.pid'
... interface = '0.0.0.0:80'
... interface_ssl = '0.0.0.0:443'
...
... host 'example.org' {
...     path '/' {
...         rate_limit = 30
...     }
... }
```

```
... host 'protected.example.org' {
...     enable_ssl = yes
...
...     path '/files' {
...         enable_auth = yes
...         user 'foo' {
...             password = 'bar'
...         }
...     }
... }
...
...
>>> from confiture import Confiture
>>> from myconfschema import MyWebserverConfiguration
>>> parsed_conf = Confiture(conf, schema=MyWebserverConfiguration()).parse()
>>> print 'daemon:', parsed_conf.get('daemon')
True
>>> for vhost in parsed_conf.subsections('host'):
...     print vhost.args
...     if vhost.get('enable_ssl'):
...         print '    SSL enabled'
...     for path in vhost.subsections('path'):
...         print '        ' + path.args
...         if path.get('enable_auth'):
...             print '            Following users can access to this directory:'
...             for user in path.subsections('user'):
...                 print '                - ' + user.args
...
example.org
/
protected.example.org
    SSL enabled
    /files
        Following users can access to this directory:
            - foo
```

Contents

3.1 Schema validation API

3.1.1 Containers

Section container

```
class configute.schema.containers.Section(**kwargs)
```

A section container used to store a mapping between name and other containers.

Parameters `**kwargs` – parameters used to override meta

Typically, this class has to be derived to specify accepted key for the section:

```
class MySection(Section):
    a_key = Value(Integer())
```

A section can also be defined imperatively:

```
>>> section = MySection()
>>> section.add('another_key', Value(Integer()))
```

Metadata

A section can hold some metadata, for example to define arguments schema or how many time the section can appear. This metadata can be defined in several different ways:

- In the `_meta` dict of a section definition (metadata are inherited from parent classes):

```
class MySection(Section):
    _meta = {'unique': True}
```

- In the `meta` dict of a section object:

```
>>> section = MySection()
>>> section.meta['unique'] = True
```

- In keyword parameters on instance initialization:

```
>>> section = MySection(unique=True)
```

Accepted metadata

args The args metadata (default None) store the container used to validate the section argument (value between the section name and the opening brace). You can use any type of container but a Section.

If the metadata is set to None (the default), argument for the section is forbidden.

Example:

```
class MySection(Section):
    _meta = {'args': Value(String())}
```

Note: This meta can't be defined for the __top__ section.

unique The unique metadata (default False) can be used to prevent multiple section to have the same arguments.

For example if you have a section with this kind of schema:

```
class MySubSection(Section):
    _meta = {'args': Value(String()), 'unique': True}

class MySection(Section):
    sub = MySubSection()
```

And a configuration file with this content:

```
sub "foo" {...}
sub "bar" {...}
sub "foo" {...}
```

The last “foo” section will throw a validation error because another “sub” section already exists with this argument.

Note: This meta can't be defined for the __top__ section.

repeat The repeat metadata (default to (1, 1)) allow to define how many time the section can appear. The first value is the minimum number of times, and the second the maximum number of time.

Values must be non-negative integers, and the first must be smaller or equal to the second. The second value can be set to None to express the infinite value.

Examples:

- (1, 1): the section must appear once
- (1, 2): the section must appear one or two times
- (0, 1): the section is optionnal and can appear once
- (0, None): the section is optionnal and can appear an infinite number of times
- (1, None): the section must appear at least once

Some shortcut are available in the confiture.schema.containers module:

- once -> (1, 1)
- many -> (0, None)

Note: This meta can't be defined for the `__top__` section.

allow_unknown The `allow_unknown` metadata (default to `False`) allow the user to set value which are not defined in the section schema. Unknown data are then available in the validated section.

Value container

```
class configure.schema.containers.Value (value_type, default=<object object>, **kwargs)
A value container used to store a scalar value of specified type.
```

Parameters

- **value_type** – the type of the value stored by container
- **default** – the default value of the container

Choice container

```
class configure.schema.containers.Choice (choices, default=<object object>, **kwargs)
A choice container used to store a choice of acceptable values.
```

This container take a choices dict where each key is one of the acceptable values, and the according value, the value returned when the key is chosen.

Parameters

- **choices** – the choices dict
- **default** – the default value of the container

List containers

```
class configure.schema.containers.List (values_type, default=<object object>, **kwargs)
A list container used to store a list of scalar value of specified type.
```

Parameters

- **values_type** – type of values
- **default** – the default value of the container

Array containers

```
class configure.schema.containers.Array (size, *args, **kwargs)
```

An array container used to store a fixed size list of scalar values of the specified type.

Parameters

- **size** – size of the array
- ****kwargs** – same arguments as List

```
class configure.schema.containers.TypedArray (values_types,      default=<object      object>,
                                            **kwargs)
```

An array container used to store a fixed size list of scalar values with specified type for each of them.

Parameters

- **values_types** – types of each item in a list
- **default** – the default value of the container

3.1.2 Types

String based types

class confiture.schema.types.**String** (*encoding=None*)

A type representing a string in the configuration.

Example in configuration:

```
my_string = "hello, world!"
```

class confiture.schema.types.**Regex** (*regex, error="value doesn't match", **kwargs*)

A string based type validated against a regex.

class confiture.schema.types.**NamedRegex** (*regex, error="value doesn't match", **kwargs*)

A string based type like Regex but returning named groups in dict.

class confiture.schema.types.**RegexPattern** (*flags=0, **kwargs*)

A re Python object.

Parameters **flags** – python re compile flag

Example in configuration:

```
match = '/[a-z]+(-[a-z]+)?\\.css'
```

class confiture.schema.types.**IPAddress** (*version=None, **kwargs*)

A string based type representing an ipv4 or ipv6 address.

This type require the “ipaddr” package to work and will return an ipaddr.IPAddress object.

Parameters **version** – type or ip address to validate, can be 4 (ipv4 addresses only), 6 (ipv6 addresses only), or None (both).

Example in configuration:

```
interface = "127.0.0.1"
```

class confiture.schema.types.**IPNetwork** (*version=None, **kwargs*)

A string based type representing an ipv4 or ipv6 network.

This type require the “ipaddr” package to work and will return an ipaddr.IPNetwork object.

Parameters **version** – type or ip address to validate, can be 4 (ipv4 addresses only), 6 (ipv6 addresses only), or None (both).

Example in configuration:

```
allow = "10.0.0.0/8"
```

class confiture.schema.types.**Url** (*encoding=None*)

A string based type representing an URL.

This type return an urlparse.ParseResult object.

Example in configuration:

```
proxy = "http://proxy:3128"
```

```
class configure.schema.types.IPSocketAddress (default_addr='127.0.0.1', default_port=None, version=None, **kwargs)
```

A string based type representing an (ip address, port) couple.

This type return an IPSocketAddress.Address object.

Example in configuration:

```
interface = "0.0.0.0:80"
```

```
class configure.schema.types.Eval (locals=None, globals=None, **kwargs)
```

A string base type evaluating string as Python expression.

Example in configuration:

```
sum = 'sum(range(3, 10))'
```

Warning: This type can be dangerous since any Python expression can be typed by the user, like `__import__("sys").exit()`. Use it at your own risk.

```
class configure.schema.types.Path (encoding=None)
```

A string representing a filesystem path.

It will expand ‘~’ to user home directory and return an absolute path if you provide a relative path (this is usefull if you change the working directory of a process after configuration parsing).

Number based types

```
class configure.schema.types.Integer (min=None, max=None)
```

A type representing an integer in the configuration.

Parameters

- **min** – define the minimum acceptable value value of the integer
- **max** – define the maximum acceptable value value of the integer

Example in configuration:

```
my_integer = 42
my_integer = 42.0 # Will also match this type
```

```
class configure.schema.types.Float
```

A type representing a float in the configuration.

Example in configuration:

```
my_float = 42.2
my_float = 42 # All values matched by the Integer type also match
# for the Float type
```

Boolean based types

```
class configure.schema.types.Boolean
```

A type representing a boolean value in the configuration.

Example in configuration:

```
my_boolean = yes
```

3.1.3 Argparse integration

Confiture provide an optionnal integration with the standard `argparse` module. This compatibility brings you a way to override some configuration values using a command line argument.

Define the schema

Each compatible Container can take five optionnals arguments:

- `argparse_names`: the list of argument names or flags, the usage of this argument enable feature for the container.
- `argparse_metavar`: the metavar value of the argument (read the argparse documentation for more informations).
- `argparse_help`: the help to display.
- `argparse_names_invert`: only for a flag value, create an argument to invert the boolean value (eg: for a `--daemon` argument, you can create a `--foreground` value which will force to disable the daemonization).
- `argparse_help_invert`: help message for the invert argument.

Example:

```
debug = Value(Boolean, argparse_names=['-d', '--debug'],
              argparse_help='enable the debug mode')
```

Populate the argument parser and use it

Once your schema is defined, you must call the `populate_argparse()` method providing the argument parser to populate:

```
parser = argparse.ArgumentParser()
schema = MySchema()
schema.populate_argparse(parser)
args = parser.parse_args()
config = Confiture(conf, schema=schema)
my_config = config.parse()
```

Full featured example

```
from pprint import pprint
import argparse

from confiture import Confiture
from confiture.schema import ValidationError
from confiture.parser import ParsingError
from confiture.schema.containers import Section, Value, List
from confiture.schema.types import Boolean, String
```

```

config_test = '''
debug = no
paths = '/bin', '/usr/bin'
'''

class MySchema(Section):

    debug = Value(Boolean(), argparse_names=['-d', '--debug'],
                  argparse_help='enable the debug mode',
                  argparse_names_invert=['-q', '--quiet'],
                  argparse_help_invert='disable the debug mode')
    paths = List(String(), argparse_names=['--paths'],
                 argparse_help='list of paths to inspect')

if __name__ == '__main__':
    # 1. Create the argument parser:
    argument_parser = argparse.ArgumentParser()

    # 2. Create the schema:
    schema = MySchema()

    # 3. Populate the argument parser using schema:
    schema.populate_argparse(argument_parser)

    # 4. Parse command line arguments
    args = argument_parser.parse_args()

    # 5. Create the configuration parser:
    config = Confiture(config_test, schema=schema)

    # 6. Parse the configuration and show it:
    try:
        pconfig = config.parse()
    except (ValidationError, ParsingError) as err:
        if err.position is not None:
            print(str(err.position))
            print(err)
        else:
            pprint(pconfig.to_dict())

```

And an execution example:

```

$ ./argparse_example.py --help
usage: ./argparse_example.py [-h] [-d] [--paths [PATHS [PATHS ...]]]

optional arguments:
-h, --help            show this help message and exit
-d, --debug           enable the debug mode
-q, --quiet           disable the debug mode
--paths [PATHS [PATHS ...]]
                     list of paths to inspect

$ ./argparse_example.py
{'debug': False, 'paths': ['/bin', '/usr/bin']}
$ ./argparse_example.py -d
{'debug': True, 'paths': ['/bin', '/usr/bin']}
$ ./argparse_example.py --paths
{'debug': False, 'paths': []}

```

```
$ ./argparse_example.py --paths /sbin /usr/sbin
{'debug': False, 'paths': ['/sbin', '/usr/sbin']}
```

3.2 Tips ‘n Tricks

3.2.1 Validate plugins configuration

If your application use a plugin system, and you want to validate a configuration which can be different for each plugin, this trick is for you.

The idea is pretty simple, do a two-step validation: the first one will validate all the common configuration, and the second step validate each plugin’s configuration. To avoid ValidationError in the first step, you use the `allow_unknown` feature of Sections.

Here is a full example:

```
import sys
from pprint import pprint

from confiture import Confiture
from confiture.schema import ValidationError
from confiture.parser import ParsingError
from confiture.schema.containers import Section, Value, many
from confiture.schema.types import Boolean, Integer, String

#
# Our Confiture schemas:
#

class GenericPluginSchema(Section):

    # This value is common to all plugins:
    common_value = Value(Integer())

    # Enable the allow_unknown meta in order to keep unknown values
    # on the first validation:
    _meta = {'allow_unknown': True,
             'repeat': many,
             'args': Value(String())}

class MainConfigurationSchema(Section):

    global_value = Value(Integer())
    plugin = GenericPluginSchema()

    #

    # Our plugins:
    #

class BasePlugin(object):

    name = None
    schema = None
```

```

def __init__(self, config):
    self.config = config

def print_config(self):
    print '%s: %s' % self.__class__.__name__
    pprint(self.config.to_dict())


class BeautifulSchema(GenericPluginSchema):

    beautiful_value = Value(String())

    # The allow_unknown meta is disable to forbid bad config:
    _meta = {'allow_unknown': False}

class BeautifulPlugin(BasePlugin):

    name = 'beautiful'
    schema = BeautifulSchema()


class UglySchema(GenericPluginSchema):

    ugly_value = Value(Boolean())
    _meta = {'allow_unknown': False}

class UglyPlugin(BasePlugin):

    name = 'ugly'
    schema = UglySchema()


#
# Our test config
#
TEST_CONFIG = '''
global_value = 42

plugin 'beautiful' {
    common_value = 123
    beautiful_value = "I'm so beautiful"
}

plugin 'ugly' {
    common_value = 456
    ugly_value = no
}
'''

#
# This is where the magic happen:
#
if __name__ == '__main__':

```

```
my_plugins = (BeautifulPlugin, UglyPlugin)
enabled_plugins = []

# Parse the global configuration:
config = Confiture(TEST_CONFIG, schema=MainConfigurationSchema())
try:
    pconfig = config.parse()
except (ValidationError, ParsingError) as err:
    if err.position is not None:
        print str(err.position)
    print err
    sys.exit(1)
else:
    print 'Main configuration:'
    pprint(pconfig.to_dict())

# Enable each used plugin:
for plugin_conf in pconfig.subsections('plugin'):
    # Search the plugin:
    for plugin in my_plugins:
        if plugin.name == plugin_conf.args:
            break
    else:
        print 'Unknown plugin %r, exiting.' % plugin_conf.args
        sys.exit(1)
    # Check plugin configuration:
    try:
        validated_conf = plugin.schema.validate(plugin_conf)
    except ValidationError as err:
        print 'Bad plugin configuration:'
        if err.position is not None:
            print str(err.position)
        print err
        sys.exit(1)
    else:
        # Instantiate the plugin object:
        enabled_plugins.append(plugin(validated_conf))

# Print each enabled plugin config:
for plugin in enabled_plugins:
    print '\n' + '~' * 80 + '\n'
    plugin.print_config()
```

And the output:

```
Main configuration:
{'global_value': 42,
 'plugin': [{'beautiful_value': "I'm so beautiful", 'common_value': 123},
            {'common_value': 456, 'ugly_value': False}]}
```

```
~~~~~
BeautifulPlugin:
{'beautiful_value': "I'm so beautiful", 'common_value': 123}
```

```
~~~~~
UglyPlugin:
```

```
{'common_value': 456, 'ugly_value': False}
```


Indices and tables

- genindex
- modindex
- search

A

Array (class in confiture.schema.containers), [9](#)

B

Boolean (class in confiture.schema.types), [11](#)

C

Choice (class in confiture.schema.containers), [9](#)

E

Eval (class in confiture.schema.types), [11](#)

F

Float (class in confiture.schema.types), [11](#)

I

Integer (class in confiture.schema.types), [11](#)

IPAddress (class in confiture.schema.types), [10](#)

IPNetwork (class in confiture.schema.types), [10](#)

IPSocketAddress (class in confiture.schema.types), [11](#)

L

List (class in confiture.schema.containers), [9](#)

N

NamedRegex (class in confiture.schema.types), [10](#)

P

Path (class in confiture.schema.types), [11](#)

R

Regex (class in confiture.schema.types), [10](#)

RegexPattern (class in confiture.schema.types), [10](#)

S

Section (class in confiture.schema.containers), [7](#)

String (class in confiture.schema.types), [10](#)

T

TypedArray (class in confiture.schema.containers), [9](#)

U

Url (class in confiture.schema.types), [10](#)

V

Value (class in confiture.schema.containers), [9](#)